

IQAir HealthPro Series



Technical Specifications & Comparison Sheet

| | HealthPro Compact | HealthPro | HealthPro Plus |
|---------------------------------|--|--|---|
| Selectable Fan Speeds | 6 | 6 | 6 |
| Air Delivery per Speed | 1 - 45 cfm 2 - 75 cfm 3 - 115 cfm 4 - 150 cfm 5 - 180 cfm 6 - 240 cfm | 1 - 45 cfm 2 - 75 cfm 3 - 115 cfm 4 - 150 cfm 5 - 180 cfm 6 - 260 cfm | 1 - 40 cfm 2 - 70 cfm 3 - 110 cfm 4 - 140 cfm 5 - 170 cfm 6 - 240 cfm |
| Maximum Coverage Area | 900 sq ft (based on maximum fan speed and an 8.5 ft ceiling) | 1100 sq ft (based on maximum fan speed and an 8.5 ft ceiling) | 900 sq ft (based on maximum fan speed and an 8.5 ft ceiling) |
| System Efficiency for Particles | 99.97% at 0.3 microns 99.5% for smaller particles | 99.97% or more at 0.3 microns 99.5% for smaller particles | |
| Power Requirements | 115 V, 50-60 Hz . All electrical components are UL certified. | | |
| Energy Consumption | 1 - 85 W / 2 - 120 W / 3 - 150 W / 4 - 170 W / 5 - 205 W / 6 - 215 W | | |
| Dimensions | H 23" W 15" D 16" | H 28" W 15" D 16" | H 28" W 15" D 16" |
| Net Weight (incl. filters) | 25 lbs | 29 lbs | 35 lbs |
| Warranty Period | 5 years on unit including fan motor, excluding filters | | |
| Filter Configuration | 1 Pre-Filter (PreMax) 1 Cleanroom-grade HEPA filter (HyperHEPA) | | 1 Pre-Filter (PreMax) 1 Gas and Odor Filter (V5-Cell) 1 Cleanroom-grade HEPA filter (HyperHEPA) |
| Average Filter Life | PreMax Filter: 6-18 months * HyperHEPA Filter: 2-4 years * (* Based on 10 hours usage per day on speed setting 3) | | PreMax: 6-18 months * V5-Cell: 1-2 years * HyperHEPA: 2-4 years * |
| Housing Material | ABS(UV-stabilized), non-offgasing, high-impact resistant | | |
| Color of Housing/Arms | Light Gray/White | | |
| Air Intake | Two side openings at base of unit | | |
| Air Outlet | Via diffuser with horizontal 320 degree, 77 sq. inch opening on top of unit | | |
| Fan Motor | Backward curved centrifugal design, 700 cfm free flow capacity, 2745 rpm, 3rd generation low noise design (Red Label), maintenance-free steel ball bearings, UL/CSA registered | | |
| Control Panel Design | 4 key touch pad, 32 character LCD display | | |
| Control Panel Key features | Display of air delivery for each speed, display of remaining filter life, automatic timer | | |
| Display Languages | English, French, German, Italian, Spanish | | |
| Supplied with | Remote Control (includes Batteries), handsigned Certificate of Performance, 6-foot power cord, set of 4 casters , user manual, user guide instructional DVD | | |